

Integrated Balustrade

Product Information

- Thermally broken aluminium frames
- Finished in a tough and long lasting polyester powder coated paint
- Fully tested to BS6180
- No top or bottom rails obstructing the view
- System fixed into the main structure of the building

Testing

Tested to BS 6180:2011 - Barriers in and about buildings

Lead time

Frame Only: 5-7 working days

Including Glass: 3-4 weeks

Installation

Screw the vertical rails to the sides of the door/tilt & turn, with 2 screws top and bottom of each rail. Install the door making sure it is square and plum within the tolerance of 2mm max.

Fix the door in 3 places, 150mm from bottom/ 150mm from top and centre, fixing through the door and rail into the structure of the building. Making sure it is packed correctly and firmly fixed.

Shuffle glaze the glass into position ensuring that the glass is 100mm higher than the frame when shuffle glazing and lower onto nylon blocks and even the glass in its frame. This should be 15mm either side into the frame.

Use wedge gasket provided to back wedge the glass so its fixed into position.

Warranty

Our products are guaranteed for 5 year parts only in accordance to our terms and conditions.

Both warranty certificate and our terms & conditions are available to download from our website.



Colours

Standard Colours:

Slate Grey RAL 7015m
Anthracite Grey RAL 7016m
Jet Black RAL 9005m
White RAL 9910m

Bespoke RAL colour also available for an additional charge.

Request a Quote:

Overall Door Width including Balustrade:

**Please note you must minus your tolerances needed*

Door height excluding cill:

Colour:

Incl Glass or Frame Only

Notes:

For more information on our range contact our team on
01420 520 580 or visit our website **www.firstglassroofs.com**

