

# Frameless Flat Rooflight

## Product Information

- Thermally broken aluminium comprising of 2 x 27mm polyamide inserts
- 48mm overhang for a better weather tight seal
- Glass from 1.0 U value to 0.2
- Available in Double Glazed or Triple Glazed
- Solar Control Self Cleaning Glass included as a standard
- No External Fixings

## Testing

- Weathertightness in accordance with BS 6375-1:2015
- Air Permeability test in accordance with BS EN 1026:2000
- Watertightness test in accordance with BS EN 1027:2000
- Resistance to wind load in accordance with BS EN 12211:2000

## Lead time

Standard Specification: 14-16 working days  
Heat Soaking: 3-4 weeks  
Toughened Laminate: 4 weeks

## Installation

To ensure a better weathertightness, there are no external fixings on our Flat Rooflights.

Our Flat Rooflight will be supplied with metal fixings straps which are screwed into the internal timber upstand and then covered over with plasterboard to ensure the perfect frameless look.

Minimum pitch: 5 degrees  
Maximum pitch: 45 degrees

Full fitting guides will be supplied with every Rooflight and are available to download from our website.

## Warranty

Our Rooflights are guaranteed for 5 year parts only in accordance to our terms and conditions.

Both warranty certificate and our terms & conditions are available to download from our website.



## Colours

Standard Colours:

Anthracite Grey RAL 7016m  
Jet Black RAL 9005m

Dual colour (white internal) also available for an additional charge.

Bespoke RAL colour also available for an additional charge.

## Request a Quote:

Internal Kerb Size:

and/or

External Kerb Size:

Colour:

Double Glazed  or, Triple Glazed

Fully Bonded  or, Manufactured Frame Only

Notes:

For more information on our range contact our team on  
**01420 520 580** or visit our website **www.firstglassroofs.com**

